

STRATEGIC

TOOLS & EQUIPMENT COMPANY

96-piece Test Lead Kit

Part Number: **ATLK96**



This complete kit turns your testing and measuring devices into powerful automotive diagnostic tools for fault-finding on the increasing number of sensors, actuators, and electronic circuits found on today's vehicles. The set contains 96 pieces of essential test aids packed in a light-weight case. The aids are for tracing, checking, capturing, or fixing complex vehicle circuitry. It's an indispensable test aid for car diagnostics!

Contents listed on next pages















CALL 1.877.952.8665 TO ORDER!

ADDRESS: P.O. Box 579 • Excelsior • MN • 55331 • USA
WEB: www.StrategicTQ.com • E-MAIL: Info@StrategicTQ.com
PH: +1.877.952.8665 (USA) • FAX: +1.213.402.6687

STRATEGIC

TOOLS & EQUIPMENT COMPANY

96-piece Test Lead Kit: Part Number: ATLK96

Photo	Description	Qty	Application
	Piercing Clip	1pc	Pierce through insulated wires without cutting or stripping insulation for quick and easy contact .
	Test Probes	1 black & 1 red	Detachable test probes allow easy cable extension.
	Alligator Clips	1 black & 1 red	Ideal for battery terminals or clip connections.
	Variable resistor with dial indicator (10KΩ ± 10%)	1pc	New variable resistor with dial indicator. Quick and easy way of resistance adjustment without the help of a multi-meter during simulation in resistance-related sensing circuit.
	Polarity/Pulse Checker	1pc	Red or Green LED will light up when contact is made to determine the polarity. LED turns red for reverse polarity, green for correct polarity.
	LED Stroboscope	2 pcs	For checking a series of terminals for correct wiring. Also for pulse or signal comparison between injectors. LED turns red for reverse polarity, green for correct polarity.
	3-way Extension	2pcs	Female Banana socket to Dual Male Banana Plug converter. One to two-way connections.
	Airbag/SRS Simulator	4pcs	Used to confirm SRS Airbag power input by connecting it first to check for any short circuit before installing a new SRS unit. Note: This SRS simulator may burn-out during testing in event of high amperage draw of more than 0.25A; therefore, 4pcs are provided.
	Maxi Fuse Adapter	1pc	Power branch-out adapter for Maxi fuse.
	ATC Fuse Adapter	1pc	Power branch out adapter for ATC fuse. Enables the user to use the same fuse taken from the fuse box in order to have the right amperage during testing.
	Mini Fuse Adapter	1pc	Power branch-out adapter for Mini fuse. Enables the user to use the same fuse taken from the fuse box in order to have the right amperage during testing.
	Acicular Probe	2pcs	Ideal for probing connectors with small gauge wires from the connector rear end.
	Banana Cable – 1.2m	1 black & 1 red	Non-twisting cable extension with 4.0 mm banana socket connection.
	Stacking Banana Cable – 1.2m	1 black & 1 red	Non-twisting extension cable with branch-out connection.












Contents continued on next page

STRATEGIC

TOOLS & EQUIPMENT COMPANY

96-piece Test Lead Kit: Part Number: ATLK96

Contents (continued from previous page)

Photo	Description	Qty	Application
	0.8mm Flat Test Lead to Female Banana Socket	3 male, 3 female	Used on 0.8 mm flat terminal output connection.
	1.2 mm Flat Test Lead to Female Banana Socket	4 male, 4 female	Used on 1.2 mm flat terminal output connection.
	2.0 mm Flat Test Lead to Female Banana Socket	4 male, 4 female	Used on 2.0 mm flat terminal output connection.
	2.5 mm Flat Test Lead to Female Banana Socket	3 male, 3 female	Used on 2.5 mm flat terminal output connection.
	3.0 mm Flat Test Lead to Female Banana Socket	4 male, 4 female	Used on 3.0 mm flat terminal output connection.
	5.0 mm Flat Test Lead to Female Banana Socket	3 male, 3 female	Used on 5.0 mm flat terminal output connection.
	6.0 mm Flat Test Lead to Female Banana Socket	3 male, 3 female	Used on 1.5 mm round terminal output connection.
	1.5 mm Round Test Lead to Female Banana Socket	3 male, 3 female	Used on 6.0 mm flat terminal output connection.
	2.0 mm Round Test Lead to Female Banana Socket	3 male, 3 female	Used on 2.0 mm round plate terminal output connection.
	3.5 mm Round Test Lead to Female Banana Socket	3 male, 3 female	Used on 3.5 mm round terminal output connection.
	4.0 mm Round Test Lead to Female Banana Socket	3 male, 3 female	Used on 4.0 mm round terminal output connection.