

TWO POST

HEAVY-DUTY ADJUSTABLE WIDTH LIFT

AMGO BP series baseplate two post lifts are stronger and more convenient to operate than most of the lifts in the world.



TWO POST LIFT

Main Features

√ 12,000lbs capacity.

BP-12

- ✓ Dual hydraulic cylinders, designed and made on high standards, high quality seals.
- √ 4 three-stage arms are suitable for more vehicles.
- √ Aero cable used for synchronization.
- √ Self-lubricating UHMW Polyethylene sliders and bronze bush.
- √ Single-point safety release.
- √ Automatic arm restraints.
- √ Width adjustment: Distance between columns 3137mm(123 1/2") and 3000mm(118 1/8").
- √ Stackable rubber pads with 1.5", 2.5" and 5" extension adapters.
- √ Heavy duty design.



Optional saddle adapter. kits No. for light truck:20802 kits No. for heavy-duty



The stackable rubber pads package with 1.5", 2.5", 5" extension adapters.



release.



Single-point safety release makes it easier for operators to unlock both column locks from one column.




The chain protection cover prevents the chain from slipping off.



4 three-stage arms are suitable for more vehicles.

SPECIFICATIONS



Model		BP-12
Lifting Capacity		12,000lbs (5500kg)
Lifting Time		65S
Lifting Height	Α	73 1/4" ~ 82 1/4" (1860 ~ 2089mm)
Overall Height	В	122 1/2" (3110mm)
Overall Width	С	145 3/8"/150 3/4" (3692/3829mm)
Drive-Thru Clearance	D	104 1/2"/109 7/8" (2653/2790mm)
Width Between Columns	Е	118 1/8"/123 1/2" (3000/3137mm)
Minimum Pad Height	F	4 3/4" (120mm)
Gross Weight		2,150lbs (975kg)
Motor		2.0HP,220V/60Hz,single phase

AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211, USA

